



Wkręty samowierzące samogwintujące Self drilling, self tapping screws | Selbstbohrende, Selbstschneidende Schrauben

WKRETY SAMOWIERCĄCE


łeb talerzykowy płaski, ocynkowane

SELF DRILLING SCREWS

flat wafer head, hardened, zinc plated

SELBSTBOHRENDE TELLERKOPFSCHRAUBEN

gehärtet, verzinkt



TYPE: WSTWC

d × L (mm)		index			index	
Steel Σti [mm] 2,25						
4,2 × 13	PH2	201213	500	6000	201213-L	10000
4,2 × 16		201216	500	6000	201216-L	10000
4,2 × 19		201219	500	6000	201219-L	10000
4,2 × 25		201225	500	6000	201225-L	6000
4,2 × 30		201230	500	6000	201230-L	5000
4,2 × 32		201232	500	6000	201232-L	5000
4,2 × 38		201238	500	6000	201238-L	4500
4,2 × 45		201245	250	3000	201245-L	4000
4,2 × 50		201250	250	3000	201250-L	3500
4,2 × 65		201265	250	3000	201265-L	2500

d × L (mm)		index		
4,2 × 13	PH2	201213-F	200	4000
4,2 × 16		201216-F	200	4000
4,2 × 19		201219-F	200	4000
4,2 × 25		201225-F	200	4000
4,2 × 30		201230-F	200	4000
4,2 × 32		201232-F	200	4000
4,2 × 38		201238-F	100	2000

WKRETY SAMOWIERCĄCE


łeb talerzykowy płaski, fosfatoryzowane

SELF DRILLING SCREWS

flat wafer head, hardened, black phosphated

SELBSTBOHRENDE TELLERKOPFSCHRAUBEN

gehärtet, schwarz phosphatiert



TYPE: WSTWF

d × L (mm)		index			index	
Steel Σti [mm] 2,25						
4,2 × 13	PH2	201213FOS	500	6000	201213FOS-L	10000
4,2 × 16		201216FOS	500	6000	201216FOS-L	10000
4,2 × 19		201219FOS	500	6000	201219FOS-L	10000
4,2 × 25		201225FOS	500	6000	201225FOS-L	6000